



THERMAL PERFORMANCE VALUES

325 SERIES > CASEMENT / AWNING / FIXED(see notes at end)

CASEMENT	U Value	SHGC	Vt	ER
Dual Pane - Low-E / Hard Coat	0.31	0.50	0.51	30
Dual Pane - Low-E / Soft Coat	0.29	0.29	0.49	21
Dual Pane - Low-E 366	0.28	0.19	0.44	16
Triple Pane - Low-E / Hard Coat x 2	0.22	0.39	0.43	35
Triple Pane - Low-E / Soft Coat x 2	0.20	0.25	0.39	29
Super Quad	0.17	0.21	0.28	31

AWNING	U Value	SHGC	Vt	ER
Dual Pane - Low-E / Hard Coat	0.31	0.50	0.51	30
Dual Pane - Low-E / Soft Coat	0.29	0.29	0.49	21
Dual Pane - Low-E 366	0.28	0.19	0.44	16
Triple Pane - Low-E / Hard Coat x 2	0.22	0.40	0.43	36
Triple Pane - Low-E / Soft Coat x 2	0.20	0.25	0.39	30
Super Quad	0.17	0.21	0.28	31

HIGH PROFILE FIXED	U Value	SHGC	Vt	ER
Dual Pane - Low-E / Hard Coat	0.30	0.56	0.59	36
Dual Pane - Low-E / Soft Coat	0.26	0.33	0.57	
Dual Pane - Low-E 366	0.26	0.22	0.51	20
Triple Pane - Low-E / Hard Coat x 2	0.19	0.44	0.49	41
Triple Pane - Low-E / Soft Coat x 2	0.17	0.28	0.45	35
Super Quad	0.13	0.23	0.32	37

LOW PROFILE FIXED	U Value	SHGC	Vt	No ER
Dual Pane - Low-E / Hard Coat	0.31	0.62	0.66	No ER
Dual Pane - Low-E / Soft Coat	0.28	0.36	0.63	No ER
Dual Pane - Low-E 366	0.27	0.24	0.57	No ER
Triple Pane - Low-E / Hard Coat x 2	0.20	0.49	0.55	No ER
Triple Pane - Low-E / Soft Coat x 2	0.17	0.31	0.50	No ER
Super Quad	0.13	0.26	0.35	No ER

Note: All values have been verified by the NFRC and Energy Star Canada. The reader is cautioned that test results should be used for comparison purposes only. Results are size and installation dependent.

For recommendations as to what glazing configurations are best suited for your application, please feel free to contact us.

For a full listing of thermal performance values, visit www.NFRC.org. All information can be found in the "Certified Products Directory". Please feel free to contact us if any assistance is required.

INLINE also complies with all North American Energy Star zoning requirements.

